

FVEP SCREW COUPLINGS

CONNECT AND DISCONNECT WITH UP TO 5,075 PSI RESIDUAL PRESSURE



- Zinc Nickel Plated Carbon Steel
- Rated for 1,200 Hours Protection Against White and Red Rust
- Large body size 1/2" to 1-1/4"
- Operating temperatures with Nitrile Seals: -40°F to 223°F
- Screw Thread Connection Eliminates Brinelling
- Orange Seal for Proper Connection Verification
- Socket Sleeve can be Pushed Back for Access to the Mating Face
- Flat Face Design Prevents Fluid Loss During Disconnection

Mobile Hydraulic Equipment OEMs & Aftermarket



 $20 = 1-\frac{1}{4}$ " Body Size

158.5 132.1 **FVEP-20** 105.7 79.3 66.0 52.8 FVEP-16 39.6 FVEP-12 **26.4** 21.1 18.4 FVEP-08 10.5 7.9 6.6 5.2 4.0 58.0 72.5 87.0 101.5 4.4 5.8 7.2 8.7 29.0 36.2 43.5 $12ORB = 1-\frac{1}{16}$ " Female ORB Hydraulic Oil PSI 16ORB = 1-5/16" Female ORB Viscosity: 32 cst = Optimum Flow Rate

PRESSURE DROP CHARACTERISTICS



200RB = 1-5/8" Female ORB



FVEP SCREW COUPLINGS

CONNECT AND DISCONNECT WITH UP TO 5,075 PSI RESIDUAL PRESSURE

Part No.	Туре	Finish	Body Size	Thread Size	Max. Working Pressure Psi	Socket Burst Pressure Psi	Plug Burst Pressure Psi	Combined Burst Pressure Psi	Weight Each (lbs)
FVEP-08S-08	Socket	Zinc Nickel Plated Carbon Steel	1/2"	1/2" Female NPT	7,975	14,500	20,300	20,300	1.2
FVEP-08P-08	Plug								1.3
FVEP-12S-12	Socket	Zinc Nickel Plated Carbon Steel	3/4"	³/ ₄ " Female NPT	7,975	14,500	20,300	20,300	1.7
FVEP-12P-12	Plug								1.5
FVEP-12S-12ORB	Socket			1-1/ ₁₆ "-12 Female ORB					1.6
FVEP-12P-12ORB	Plug								1.4
FVEP-16S-12	Socket	Zinc Nickel Plated Carbon Steel	1"	³/ ₄ " Female NPT	7,250	15,225	20,300	20,300	2.5
FVEP-16P-12	Plug								2.3
FVEP-16S-12ORB	Socket			1-1/ ₁₆ "-12 Female ORB					2.5
FVEP-16P-12ORB	Plug								2.3
FVEP-16S-16	Socket			1" Female NPT					2.4
FVEP-16P-16	Plug								2.3
FVEP-16S-16ORB	Socket			1-5/ ₁₆ "-12 Female ORB					2.4
FVEP-16P-16ORB	Plug								2.2
FVEP-20S-20	Socket	Zinc Nickel Plated Carbon Steel	1-1/4"	1-1/4" Female NPT	6,815	14,500	18,850	18,850	3.8
FVEP-20P-20	Plug								3.2
FVEP-20S-20ORB	Socket			1-5/ ₈ "-12 Female ORB					3.8
FVEP-20P-20ORB	Plug								3.2

