



PUSH BUTTON SAFETY VENT SOCKETS

ZERO PRESSURE CONNECT AND DISCONNECT DESIGN | ONE-HAND OPERATION



Features and Benefits:

- Industrial Interchange, Pneumatic Application
- Anodized aluminum body for long life
- Push twice for release: first push vents, second releases
- Swivel Body to Keep Hose Untangled
- ISO 4414 Norm
- **Button, valve, & venting ring:** Hardened zinc-plated steel
- **Springs, balls:** Stainless Steel
- **Flow capacity:** 37SCFM (at 90 psig with connected insert)
- **Recommended working temperature:** 0°F to 160°F
- **Max working pressure:** 175 psi (safety factor 4:1)

Female Pipe Thread Industrial Interchange		Part No.	Size	Description
		SPB3003	1/4"	1/4" Body, Safety Push Button
		SPB4204	3/8"	3/8" Body, Safety Push Button

Male Pipe Thread Industrial Interchange		Part No.	MPT	Description
		SPB3103	1/4"	1/4" Body, Safety Push Button
		SPB4304	3/8"	3/8" Body, Safety Push Button

SV & SVPC Series Safety Vent Couplers (Industrial Interchange)

Steel	Protective Covered (PC) Body	Fully Protective Covered (PC)	Fully Protective Covered (PC) w/Strain Relief
			

