



# DURABLE FLAT-FACED COUPLERS

EASILY CONNECT AND DISCONNECT HYDRAULIC HOSES FROM SALT TRUCKS AND SNOW PLOWS!



**Foster's Flat-Faced Couplers** are tested to 1,200 hours of protection from white & red rust. These easy-to-disconnect couplers are designed to minimize air inclusion upon connection and include a sleeve-lock to prevent accidental disconnection. These couplers are manufactured to ISO 16028 and are available in a variety of options, including connect under pressure versions, NPT and ORB thread types, and zinc-nickel plating at no additional cost.

## Features and Benefits

- Stainless Steel Viton Seals have an operating temperature of -4degreesF to 392degreesF
- Zinc Nickel Plated Steel Nitrile Seals have an operating temperature of -40degreesF to 223degreesF
- Available in 316 Stainless Steel
- Available in Connect Under Pressure Versions
- Zinc-Nickel Plating at no additional cost
- Multiple thread types: NPT and ORB
- Manufactured to ISO 16028
- Steel Body Sizes: 1/4" - 1-1/2"
- 316SS Body Sizes: 1/4" - 1"



***Pictured after full season of plowing and salt spraying in Clinton County, MI!***

**Also available in FVEP Screw-On Flat Face Couplings in Zinc-Nickel Plated Steel for Hydraulic Hose Connections!**



**"The Foster FF Plus couplers didn't show any white or red rust after a full season of use. They connected and disconnected easily without any leakage."**

*Clinton County, MI Road Commission Supervisor*

